



Walk –Behind Slaw Saws

K2 1610 B SLAB SAW SERIES

K2-1610B ELECTRIC Walk-behind Slab Saw

The K2-1610B walk-behind concrete saws feature a one-piece box construction chassis made from 3/16" hot-rolled steel that will not flex during operation. Powder-coated chassis resists peeling and corrosion. The blade guard mounts on both the left and right side of saw and cuts within 2" of wall or curb.

- Arbor Size 1" (25 mm)
- L x W x H (inches) 42" x 25" x 39"
- L x W x H (mm) 1,067 x 635 x 991
- Model / K2-1610B
- Motor / Baldor (Electric)
- Power / 10 Hp 230V or 460V 3 Ph
- Blade Capacity / 18" (457mm)
- Depth of Cut 6-5/8" (168 mm)
- Weight 275 lbs. (125 kg)
- Built-in Depth Gauge
- Power cord with connector
- Lifting Bail
- Optional 6.5 Gallon Water Tank

Totally enclosed fan cooled (TEFC) 3 phase, 10 Hp Baldor motor providing 29.5 ft-lb of torque
" NEMA 12 across the line starter switch

" One-piece box construction chassis made from 3/16" hot-rolled steel will not flex during operation
" Powder-coated chassis resists peeling & corrosion

" Cast-aluminum hinged blade guard
" Stainless steel water distribution system supplies water to both sides of blade

" 18+blade guard mounts on both left- or right-hand side of saw and cuts within 2" of wall or curb
" 1-1/4" blade shaft supported by two heavy-duty, self aligning pillow block bearings

" Depth control assembly engineered for smooth, controlled blade insertion

" Durable 8" x 2-1/4" non-slip rubber wheels with maintenance-free hubs & roller bearings
" Positive-locking depth control mechanism

" Built-in depth gauge, power cord with connector and lifting bale

" One-year limited warranty

✉ 23911 Garnier St. #C Torrance, CA 90505 | ☎ 1.800.539.6116 | ✉ K2diamond@sbcglobal.net | ☎ 310.539.5495