



K220HSP

# K220HSP & K220KPSP Series Self-Propelled Concrete Saws

## Features

- ◆ Industrial 1 3/16" blade shaft assembly by two heavy-duty, self-aligning pillow block bearings with easy access grease fittings
- ◆ **Built-in tachometer/hour meter**
- ◆ Depth feed gauge indicator
- ◆ One piece box construction chassis made from 3/16" hot rolled steel will not flex during operation
- ◆ **Powder coated chassis** resists peeling and corrosion
- ◆ Two piece cast aluminum guard assembly
- ◆ Front pivot design allows cutting into walls and curbs
- ◆ Stainless steel water cooling nozzles
- ◆ Blade guard can be positioned for left or right hand cutting
- ◆ Heavy-duty **hydro static transmission** with variable speed drive
- ◆ Durable 8" x 2 1/4" non-slip rubber wheels with maintenance free hubs and roller bearings
- ◆ Positive ball bearing screw feed depth feed with hand crank
- ◆ Open loop propane system and 5 gallon (20 lb. tank) propane bottle on MK-2020KSP
- ◆ Forward travel speed: 0 - 80'/min.
- ◆ One year limited warranty



Blade Guard can be positioned for left or right hand cutting



Heavy-duty hydro static transmission with variable speed drive



Front nose of blade guard can be rotated up for easy blade removal



User friendly control panel

# K220HSP & K220KPSP Series

## Self-Propelled Concrete Saws



| MODEL                    | K220HSP                                     | K220KPSP                                     |
|--------------------------|---------------------------------------------|----------------------------------------------|
| Engine                   | Honda Twin - V                              | Kohler Propane                               |
| Horsepower               | 20                                          | 20                                           |
| Fuel Capacity            | 2 gallons                                   | 5 gallons (20 lb. tank)                      |
| Blade Capacity           | 20"                                         | 20"                                          |
| Blade RPM                | 3600                                        | 3600                                         |
| Arbor Size               | 1"                                          | 1"                                           |
| Depth of Cut (20" blade) | 7 5/8"                                      | 5 5/8"                                       |
| Weight                   | 392 lbs.                                    | 417 lbs.                                     |
| LxWxH                    | 65 x 26 x 37 (in.)<br>1651 x 660 x 940 (mm) | 65 x 26 x 47 (in.)<br>1651 x 660 x 1194 (mm) |
| Part#                    | 113394                                      | 113395                                       |

### Included Accessories



Lifting Bail



5 gal. Propane Bottle and holder (K220KPSP)

### Optional Accessories



Electrical Water Pump



6.5 Gallon water tank