Walk –Behind Slaw Saws

K2—3000B Electric Self-Propelled Slab Saws

The K2-3000 Electric Saw provides a solution for those environments and situations where electric power is the right choice, whether for indoor use or simply operator preference. The saw utilizes a three-phase, 20 Hp, Baldor electric motor in 230V or 460V to match the user's need. The saw features the same raise/lower system, self-propelled transmission and control set as other K2-3000s.
An ammeter is provided to help monitor load when cutting.

Switch	IP 65 IEC Across the line starter			
Travel Speed	0-220 FPM Forward, 0-100 FPM Reverse			
L x W x H (inches) **L x W x H (mm)**	50" x 32" x 42" 1,270 x 813 x 1,067			
Motor	Baldor (Electric)			
Weight	700 lbs. (318 kg)			
Model	**K2-3024B**	**K2-3024B**	**K2-3030B**	**K2-3030B**
Size	24" (610 mm)	24" (610 mm)	30" (762 mm)	30" (762 mm)
Power	20 Hp 230V 3Ph	20 Hp 460V 3Ph	20 Hp 230V 3Ph	20 Hp 460V 3Ph
Blade RPM	2,020	2,020	2,020	2,020
Depth of Cut	9-1/2" (241 mm)	9-1/2" (241 mm)	12-1/2" (318 mm)	12-1/2" (318 mm)

Baldor 20HP, 3 Phase, TEFC motor, providing 30ft-lb of torque

Instrumentation includes ammeter and depth of cut indicator



7 3VX V-belt drive from engine to center shaft

23911 Garnier St. #C Torrance, CA 90505 | 1.800.539.6116 | K2diamond@sbcglobal.net | 310.539.5495