



Walk –Behind Slaw

K2 4000 B SLAB SAW SERIES

### K2-4000 Electric Series Self-Propelled Slab Saws

The K2-4000 Electric Saw provides a solution for those environments and situations where electric power is the right choice, whether for indoor use or simply operator preference. The saw utilizes a three-phase, 30 Hp, Baldor electric motor in 230V or 460V to match the user's need. The saw features the same hydraulic raise/lower system, self-propelled transmission and control set as other K2-4000s. The saw has an on-board battery to provide 12VDC power for raise/lower function when the saw is not plugged in, and has a transformer/battery charger to recharge the system automatically anytime the saw is connected to power. The saw can also be plugged into 120VAC to recharge or maintain the battery when the saw is not in use. An ammeter is provided to help monitor load when cutting.

|                           |                                      |                 |                  |                  |
|---------------------------|--------------------------------------|-----------------|------------------|------------------|
| <b>Switch</b>             | IP 65 IEC across the line starter    |                 |                  |                  |
| <b>Travel Speed</b>       | 0-220 FPM Forward, 0-100 FPM Reverse |                 |                  |                  |
| <b>L x W x H (inches)</b> | 50" x 29" x 42"                      |                 |                  |                  |
| <b>L x W x H (mm)</b>     | 1,270 x 737 x 1,067                  |                 |                  |                  |
| <b>Motor</b>              | Baldor (Electric)                    |                 |                  |                  |
| <b>Weight</b>             | 1250 lbs. (567 kg)                   |                 |                  |                  |
| <b>Model</b>              | <b>K2-4024B</b>                      | <b>K2-4024B</b> | <b>K2-4030B</b>  | <b>K2-4030B</b>  |
| <b>Blade Capacity</b>     | 24" (610 mm)                         | 24" (610 mm)    | 30" (762 mm)     | 30" (762 mm)     |
| <b>Power</b>              | 30 Hp 230V 3 Ph                      | 30 Hp 460V 3 Ph | 30 Hp 230V 3 Ph  | 30 Hp 460V 3 Ph  |
| <b>Blade RPM</b>          | 2,040                                | 2,040           | 2,040            | 2,040            |
| <b>Depth of Cut</b>       | 9-1/2" (241 mm)                      | 9-1/2" (241 mm) | 12-1/2" (318 mm) | 12-1/2" (318 mm) |

23911 Garnier St. #C Torrance, CA 90505 | 1.800.539.6116 | K2diamond@sbcglobal.net | 310.539.5495