



K213HS

Features

- ◆ Engineered for compactness, maneuverability and reliability
- ◆ **16" blade capacity** (optional 18") provides for a **5 5/8" depth of cut**
- ◆ Heavy-duty 1" dual blade shaft assembly with self-aligning pillow block bearings to ensure accurate cutting on either left or right side
- ◆ User friendly control panel
- ◆ Durable 8" x 2 1/4" **non-slip rubber wheels** with maintenance free hubs and roller bearings
- ◆ One piece box construction, powder coated chassis made from 3/16" hot-rolled steel will not flex during operation, peel or corrode
- ◆ **Powder coated chassis resists peeling and corrosion**
- ◆ Machined depth control shaft for smooth, controlled blade insertion
- ◆ Positive locking depth control mechanism
- ◆ Two-piece cast aluminum blade guard assembly with custom built-in water distribution system will not rust or bend
- ◆ Pivoting blade guard permits cuts within 1" of walls and curbs
- ◆ Built-in depth gauge, tachometer/hour meter, and lifting bail (only on premium series)
- ◆ One year limited warranty



Front nose of blade guard can be rotated up for easy blade removal

User friendly control panel

Blade guard can be positioned for left or right hand cutting

Two piece cast aluminum blade guard assembly with custom built-in distribution system will not rust or bent

K213H Series

Walk-Behind Concrete Saws



Blade Capacity	16" (350mm)
Arbor Size	1" (25mm)
Depth of Cut (16" blade, optional 18")	5 5/8" (143mm)
Blade RPM	3600
L x W x H	52 x 25 x 39 (in.) 1321 x 635 x 991(mm)

MODEL	K213HS	K213HP
Engine	Honda ¹	Honda ¹
Horsepower	13 hp	13 hp
Weight	213 lbs. (97 kg)	223 lbs. (101 kg)
Part#	113392	113393

¹Honda engines include Cyclone™ air filter and oil alert